



Supreme Ultra



Location photography courtesy of York Equestrian Centre

The generous proportions of the Ultra make the transport of two large horses easy and enjoyable for you and your horses.

Its spacious interior makes loading and unloading easy, and its internal dimensions provide comfort for your horses on journeys of all lengths. They will arrive at their destination looking and feeling their best.

Ramp lifters are fitted as standard, and the external and internal lighting maximises visibility and safety inside and out.

As with all trailers in the Supreme range, a spare wheel and cover, mounted on the side of the trailer, are standard. Also, the groom's door on the Ultra is lockable.





Supreme Ultra



Construction Specifications

- Full height front and rear unload
- Fully welded, hot dipped galvanized chassis and framework
- Resin coated pre coloured body panels
- Plastic coated roof sheets
- GRP nose cone and dome door
- Heavy duty thermoplastic mudguards
- Independent suspension complete with full width galvanized beam axles
- Braking system with auto reverse coupling
- Compliant low maintenance 12 volt lighting system
- Doors above rear ramp (travel open or closed)
- Fixed side windows
- One piece plastic floor guaranteed against rot and corrosion for life of trailer

General Specifications

- Front air vent
- Window, and roof-light in nose cone
- Interior light
- Rubber floor and ramp mats
- Removable swivel partition
- Adjustable padded breast and breech bars
- Quick release breast bar brackets
- Internal tie rings
- Partition and side padding
- Jockey wheel
- Spare wheel and cover with logo – mounted on side

Security

- Locking coupling head
- Lockable grooms door handle

Optional Extras

See price list for details

Shipton-by-Beningbrough
York YO30 1AB

T: 01904 470282 / 470315
F: 01904 470486

W: www.richardsonrice.co.uk
E: info@richardsonrice.co.uk

Technical Specification

Gross Weight	Unladen Weight	Pay Load	Tyre Size	Tyre Pressure	Overall Length	Overall Width	Overall Height
2700KG	1100KG	1600KG	165/R/13/8ply	65PSI	5000mm 16ft 5ins	2298mm 7ft 6ins	2750mm 9ft 1ins
Upgrade							
Internal Length	Internal Width	Internal Height	Max distance between Breast & Breech bars		Gross Weight	Tyre Size	
3540mm 11ft 7ins	1800mm 5ft 11ins	2330mm 7ft 8ins	2230mm 7ft 4ins		3200KG	185/R/14/8ply	