



# General Purpose Trailers



1500T



2000T



750GP

Each of the trailers in the Richardson General Purpose range is fitted with hydraulic couplings and auto reversing brakes, to meet EEC Directive number 71/320.

For durability, our steelwork is fully welded and hot dip galvanised. Capacity and loading are made easy with 16" galvanised steel sides on all models. A drop tailgate and full road lighting is standard.

Full width galvanised beam axles and independent suspension ensure easy towing and a smooth ride for every load.

## Single Axle range

Each of the trailers in the Richardson Single Axle General Purpose range of trailers is versatile and robust, designed to stand the rigours of commercial use yet towed by most family cars and light vans. They are strong and can carry a useful load, yet are light and small enough to be driven and reversed into the most inaccessible areas.

## Twin Axle range

The Twin Axle range offers the ease and speed of low-loading, generous capacity and robust build. Our trailers lighten your load with easy and economic goods handling.



Special



# General Purpose Trailers



## Single & Twin Axle

- General purpose low maintenance trailer suitable for builders, landscapers, estate managers etc.
- Suitable for carrying a wide range of equipment and materials including sand and cement, garden waste, quad bikes, lawn mowers etc.
- Fully welded, hot dipped galvanized construction for long life
- Robust and lightweight
- Independent suspension complete with full width galvanized beam axle
- Low loading height
- Braking system with auto reverse coupling
- 16inch fixed sides with a drop down tail-gate
- Compliant low maintenance 12 volt lighting system
- Locking coupling head
- Jockey wheel
- Phenolic plywood anti-slip floor
- Complete with rope hooks & 4 internal lashing rings

## Optional Extras

- Ramped tail-gate
- Detachable ladder rack
- Rear loading stands
- Spare wheel and carrier
- Mesh extension sides
- Security wheel clamp
- Folding ramp tail-gate\*\*
- Reinforced heavy duty ramped tailgate\*\*
- Ramp tail-gate lifting aid\*\*
- Manually operated winch\*\*
- Winch fixing post\*\*

\*\* = Twin axle only

## Models:

### Single Axle:

750GP  
1000GP  
1300GP  
1500GP

### Twin Axle:

1500T  
2000T  
2600T  
3500T

Shipton-by-Beningbrough  
York YO30 1AB

T: 01904 470282 / 470315  
F: 01904 470486

W: [www.richardsonrice.co.uk](http://www.richardsonrice.co.uk)  
E: [info@richardsonrice.co.uk](mailto:info@richardsonrice.co.uk)

## Technical Specification

	Gross Weight	Unladen Weight	Pay Load	Tyre Size	Tyre Pressure	Overall Length	Overall Width	Deck Length	Deck Width
<b>750GP</b>	750kg	280kg	470kg	165/R/13/8ply	65psi	3030mm/9ft 11ins	1770mm/5ft 10ins	1860mm/6ft 2ins	1215mm/4ft
<b>1000GP</b>	1000kg	320kg	680kg	165/R/13/8ply	65psi	3605mm/11ft 10ins	1770mm/5ft 10ins	2475mm/8ft 2ins	1215mm/4ft
<b>1300GP</b>	1300kg	360kg	940kg	165/R/13/8ply	65psi	3625mm/11ft 11ins	2060mm/6ft 9ins	2475mm/8ft 2ins	1530mm/5ft
<b>1500GP</b>	1500kg	400kg	1100kg	6.00x16 6ply	52psi	3625mm/11ft 11ins	2060mm/6ft 9ins	2475mm/8ft 2ins	1530mm/5ft
<b>1500T</b>	1500kg	400kg	1100kg	165/R/13/8ply	65psi	3625mm/11ft 11ins	2060mm/6ft 9ins	2475mm/8ft 2ins	1530mm/5ft
<b>2000T</b>	2000kg	440kg	1560kg	165/R/13/8ply	65psi	4200mm/13ft 11ins	2060mm/6ft 9ins	3080mm/10ft	1530mm/5ft
<b>2600T</b>	2600kg	440kg	2160kg	165/R/13/8ply	65psi	4200mm/13ft 11ins	2060mm/6ft 9ins	3080mm/10ft	1530mm/5ft
<b>3500T</b>	3500kg	720kg	2780kg	205/R/16 reinforced	44psi	4975mm/16ft 4ins	2286mm/7ft 6ins	3690mm/12ft	1828mm/6ft