



# Vehicle Transporters



HD60



16ft Tilt bed

Richardson Trailers have an enviable reputation for quality and innovation. To maximise strength and durability each of our transporters is fully welded and hot dip galvanised. All transporters have a non-slip phenolic coated plywood deck, which enables your trailer to be used as a general load carrier. This increases its versatility and its economic value.

## Car Transporters

The 14ft standard trailer is ideal for small garages, and for transporting vintage cars and tractors. With a fixed platform and ramps fitted as standard.

## Tilt Bed Transporters

The Tilt Bed Trailer is available in two sizes, with the option to upgrade to 2600kg if needed. This trailer is often supplied to main car dealers, motor sport and prestige garages for the movement of vehicles. It can easily be operated by one person with very little effort, no ramps are required. It is also ideal for recovering non-runners and accident damaged vehicles. Standard features include hydraulic tilt, winch post, underdeck rope hoops and lockable coupling.

## Heavy Duty Vehicle Transporter

The HD60 is the largest vehicle transporter in our range and is designed for professionals in the Ground Maintenance and Agricultural Machinery sectors.

Robust and sturdy, it is rated to 3.5 tonnes with a maximum load capacity of 2.65 tonnes, and is ideal for transporting compact tractors, ATVs, ride-on mowers etc.

The HD60 has a low loading height, with a 4 foot beavertail, and a 12 foot deck. It is particularly popular with Recovery Specialists. Standard features include a heavy duty jockey wheel, flat bed and ramps with underdeck stowage. An exceptionally good value for money trailer.



Special





# Vehicle Transporters



## Car Transporter Trailers 14ft and 16ft

- Fully welded, hot dipped galvanized construction
- Robust and sturdy
- Independent suspension complete with full width galvanized beam axles
- Low loading height
- Low 9 inch high side rails (allow car doors to be opened when loaded)
- Load bearing mudguards
- Braking system with auto reverse coupling
- Compliant low maintenance 12 volt lighting system
- Locking coupling head
- Jockey wheel
- Phenolic plywood anti-slip floor (Versatility for carrying accident damaged cars or other loads)
- Complete with rope hooks
- Winch fixing post
- Hydraulic tilt deck (Tilt bed models only)
- Loading ramps 6ft (14ft standard transporter only)
- Removable lighting board (14ft standard transporter only)

## Optional Extras:

- Upgrade GVW to 2600kg
- Spare wheel and carrier
- Inset deck lashing rings
- Manually operated winch
- 3m load securing straps
- Security wheel clamp

## Models:

- 14ft Standard
- 14ft Tilt bed
- 16ft Tilt bed

## Heavy Duty Beaver-Tail Transporter

- The HD60 is ideal for the transportation of ground maintenance vehicles, heavy duty machinery, compact tractors, ATV's, ride on mowers etc
- 12ft deck and 4ft beaver tail
- Low maintenance independent suspension
- Fully welded, hot dipped galvanized construction for long life
- Robust and sturdy
- Under chassis wheel design maximises usable load width
- Independent suspension complete with full width galvanized beam axles
- Braking system with auto reverse coupling
- Compliant low maintenance 12 volt lighting system
- Locking coupling head
- Phenolic plywood anti-slip floor
- Winch fixing post
- Heavy duty loading ramps 6ft

## Optional Extras:

- Upgrade to 7ft 6ins width
- Spare wheel and carrier
- Inset deck lashing rings
- Manually operated winch
- 3m load securing straps
- Security wheel clamp
- Electro-air brake servo system

## Models:

- HD60

Shipton-by-Beningbrough  
York YO30 1AB

T: 01904 470282 / 470315  
F: 01904 470486

W: [www.richardsonrice.co.uk](http://www.richardsonrice.co.uk)  
E: [info@richardsonrice.co.uk](mailto:info@richardsonrice.co.uk)

## Technical Specification

	Gross Weight	Unladen Weight	Pay Load	Tyre Size	Tyre Pressure	Overall Length	Overall Width	Deck Length	Deck Width
14ft Standard *	2000kg	600kg	1400kg	165/R/13/8ply	65psi	5655mm/18ft 6ins	2260mm/7ft 5ins	4268mm/14ft	1840mm/6ft
14ft Tilt Bed *	2000kg	620kg	1380kg	165/R/13/8ply	65psi	5655mm/18ft 6ins	2260mm/7ft 5ins	4268mm/14ft	1840mm/6ft
16ft Tilt Bed *	2000kg	660kg	1340kg	165/R/13/8ply	65psi	6264mm/20ft 6ins	2260mm/7ft 5ins	4877mm/16ft	1840mm/6ft
HD60 Beaver Tail **	3500kg	850kg	2650kg	185/70/R/13	65psi	6440mm/21ft 2ins	1980mm/6ft 6ins	4877mm/16ft	1980mm/6ft 6ins
*= can be upgraded to			2600kg	165/R/13/8ply	65psi				
**= can be upgraded to							2286mm/7ft 6in		2286mm/7ft 6in